



Castrol Rustilo 4163

Neat corrosion preventive oil

Description

Castrol Rustilo™ 4163 is an oil-dispersed and fingerprint suppression corrosion preventive formulated to give long-term indoor protection. This product deposits a thin, slightly oily residual film, which is easily cleaned using an alkaline cleaner or vapour degreaser.

Application

Use Castrol Rustilo 4163 where:

- Operations expose the metal to water-containing machining and grinding coolants, cleaners, and water rinses.
- Parts are manually inspected or packaged
- Long-term indoor humidity protection is needed.
- Ease of cleanability is desired.

Advantages

- This product will provide excellent humidity protection for ferrous and nonferrous parts for up to two years in indoor storage.
- High flash point eliminates need for special fire equipment.
- Barium-free
- Excellent resistance to acid atmosphere for ferrous and nonferrous parts, which have been stored in or near acidic environments.
- Handled parts are fully protected from fingerprint corrosion because of specially formulated additives.

Typical Characteristics

Name	Method	Units	Castrol Rustilo 4163
Appearance	Visual	-	Clear, brown fluid
Density @15C	-	g/cm ²	0.880-0.900
Viscosity, Kinematic @40C	CN-TM-101	mm ² /s	7
Flash Point (COC)	CN-TM-039	C	104-110C
Film Type	-	-	Oily
Fingerprint Suppression	MW-TM-315		Yes
Corrosion Protection	Indoor Storage Outdoor Storage	Month	12-24 indoor; Not recommended outdoor
Film Thickness		microns	2

User Advice

Recommended applications For best results, Rustilo 4163 should be applied by dip, flood or spray method.

Additional Information

- The claims on film thickness and consumption are average values. These are valid for smooth surfaces with good drain-off characteristics and simple geometries without holes or recesses.
- "Indoor storage" describes the storage of ferrous components in closed store-rooms having a relative humidity of 60%. Increased protection times could be achieved when treating finished surfaces or store the parts in a sealed pack.
- "Outdoor storage" describes open storage, which assumes primary protection from the elements by tarpaulin or other form of cover.
- Influence of temperature may cause some cloudiness, which is reversible and doesn't have an impact on product quality.
- If required protective films of Rustilo 4163 can be removed by using a petroleum solvent or alkaline process cleaner, all available from Castrol.

Castrol Rustilo 4163

04 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 352, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 9645111 Technical Enquiries: 0345 082 1719

www.castrol.com/industrial