



Product Data

Lubricity Additive N 526

Lubricity Enhancer for Neat Oils

Description

Castrol Lubricity Additive N 526 is a phosphorus containing lubricity enhancer especially formulated for neat oils. It can be used in single sump machines as well as central systems.

Application

Castrol Lubricity Additive N 526 is especially formulated for use with Castrol's neat oil range.

Conditions of Use

Castrol Lubricity Additive N 526 should only be used upon recommendation of Castrol's Service Representative. Recommended concentration is between 0,4 - 2% depending on lubrication problem.

Typical Characteristics

Properties	Standard	Unit	Data
Appearance	Visual		yellow
Viscosity @ 40°C	DIN 51562 ASTM D 445	mm ² /s	23
Density @ 20°C	DIN 51757 ASTM D 1298	kg/l	0.90
Flashpoint COC	ISO 2592 ASTM D 92	°C	126°C

Subject to usual manufacturing tolerances.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F. For more details, please refer the product safety data sheet.

Lubricity Additive N 526

31 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>