



Hyspin™ H 540

Hydraulic Oil

Description

Castrol Hyspin™ H 540 (previously called Castrol H™ 540) is a hydraulic oil specified HVLP according DIN 51502. It fulfills the specification TL 9150-0035 of the Bundesamt für Wehrtechnik und Beschaffung (Federal Office for Defence Engineering and Provision) and NATO code H 540.

Advantages

Hyspin H 540 has very good air and water separation ability, minimal foaming tendency and an optimal corrosion protection. In addition, this product has effective viscosity-temperature behaviour and a reliable ageing stability.

Typical Characteristics

	Method	Units	Hyspin H 540
Colour - Saybolt	ISO 2049 / ASTM D156	-	<2.0
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m ³	891
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	37
Kinematic Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	10.0
Viscosity Index	ISO 2909 / ASTM D2270	-	272
Pour Point	ISO 3016 / ASTM D97	°C/°F	-57/-71
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	128/262
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	11

Subject to usual manufacturing tolerances.

This product was previously called H™ 540 . The name was changed in 2015.

Hyspin™ H 540
18 Aug 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>