



Molub-Alloy 870-2

Heavy Duty Grease

Description

CASTROL MOLUB-ALLOY® 870 is a high-performance EP-Grease developed for large, slow moving, and heavily loaded rolling element bearings.

Application

CASTROL MOLUB-ALLOY® 870 was initially designed for rolling element bearings with outer diameter 600 to 1000 mm and running at 5 rpm, like they are used in cane sugar rollers. The outstanding viscosity-temperature behaviour and low stock-point of the base oil allows operating temperatures down to 0 °C.

Advantages

- The base oils are high viscosity mineral oils forming a stable lube film. Corrosion and oxidation inhibitors maximize effective rust protection and long life of the grease.
- CASTROL MOLUB-ALLOY® 870 HEAVY DUTY GREASE provides an excellent sealing effect against contamination and water.
- CASTROL MOLUB-ALLOY® lubricating solids, in conjunction with selected soluble EP additives, interact synergistically to provide additional protection against machinery component wear.

Typical Characteristics

Name	Method	Units	Molub-Alloy 870-2
Thickener type	-	-	Lithium
Worked Penetration (60 strokes @ 25°C / 77°F)	ISO 2137 / ASTM D217	0.1 mm	265-295
Dropping point	ISO 2176 / ASTM D566	°C/°F	182/359.6
Base Oil Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm ² /s	1776
Base Oil Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm ² /s	108
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	230/446
Rust Test - EMCOR (distilled water)	ISO 11007 / ASTM D6138	Rating	0/0
Timken OK Load	ASTM D2509	kg / lbs	25.5/56.2

Additional Information

CASTROL MOLUB-ALLOY® 870 can be applied manually or with grease guns.

Molub-Alloy 870-2

13 Jul 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial