



Performance Bio NC Ultra Lite

High performance neat cutting oil

Description

Castrol Performance Bio NC Ultra Lite is a chlorine free, multi-metal compatible, high performance neat cutting oil, which is based on plant oil and synthetic hydrocarbon technology. Customer feedback* has highlighted low misting characteristics, robust oxidation stability and excellent cooling properties, which can help create productivity increases.

Application

Performance Bio NC Ultra Lite is designed for drilling, gear manufacturing and general cutting operation of ferrous and non-ferrous metals.

ü ü suggested core application ü possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed steel / nickel-chromium alloys	Titanium alloys	Aluminium alloys	Yellow metals
Honing/ Superfinishing	ü	ü		ü	ü ü	ü ü
Grinding	ü	ü		ü	ü	ü
Drilling	ü ü	ü ü		ü ü	ü ü	ü ü
Broaching	ü	ü		ü ü	ü ü	ü ü
Gear manufacturing	ü ü	ü		ü ü	ü ü	ü ü
General machining	ü ü	ü ü		ü ü	ü ü	ü ü

Advantages

- Customers have commented* favorably on the low misting and smoking characteristics. This helps to reduce oil consumption.
- High oxidation stability increases product lifetime and reduce oil consumption
- Plant oil based technology shows better cooling properties than traditional mineral oils. This characteristic could help support productivity increases
- This product has shown good filtering characteristics in a 3rd party's filtration test**. This helps to extend the life of the fluid and helps to keep the working environment clean.
- Our chlorine free formulation can help reduce disposal costs
- Low odour and light colour help to improve the working environment
- Multi-metal compatibility provides opportunity for product consolidation

* Based on feedback received from our customers in the USA using Performance Bio NC fluids

** A 3rd party producer of filters for the grinding segment was asked to use their in-house test to assess whether they would approve this cutting oil for use with their products based on its filtering characteristics.

Typical Characteristics

Properties	Standard	Unit	Data
Appearance	Visual		Light Yellow
Viscosity @ 40°C	DIN 51562 ASTM D 445	mm ² /s	16
Viscosity @ 100°F	ASTM D 445	SUS	88
Flashpoint COC	ISO 2592 ASTM D 92	°C/°F	173/343
Copper corrosion	ISO 2160 ASTM D 130	3 hr at 100 °C	1b

Storage

To avoid product deterioration always keep the container/drum tightly sealed. For optimum product stability, store between 5°C/41°F and 45°C/113°F in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. It is preferable to store the product indoors.

For more details, please refer the product safety data sheet.

Performance Bio NC Ultra Lite

26 Sep 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial