

Variocut C 814 HC

High performance neat cutting oil

Description

Castrol Variocut™ C 814 HC is a neat cutting oil based on the latest generation of Extreme High Viscosity Index (EHVI) hydrocracked base oils and advanced synthetic ester technology formulated without chlorinated paraffines. It is especially developed to optimise machining performance, enhance surface finish and help to lower the overall operating costs.

Application

Variocut C 814 HC is especially designed for gear production machining of ferrous alloys.

√√ suggested core application √ possible application, please consult Castrol representative prior to use

	Cast Iron	Low-medium alloyed steel	High alloyed steel / nickel-chromium alloys	Titanium alloys	Aluminium alloys	Yellow metals
Honing/ Superfinishing						
Grinding	√√	√√	√		√	
Drilling	√	√	√		√	
Broaching/ Gear manufacturing	√√	√√	√		√	
General machining	√√	√√	√		√	

Advantages

- Low oil mist and foam characteristics, even at high pressures and flow rates, lead to a reduction in oil consumption and increased production rates
- Superior additive technology leads to extremely high cutting and grinding efficiencies, help to increased tool life, improved surface finish and lower overall operating cost
- Good filtering characteristics and high oxidation stability can increase product lifetime
- Formulated without chlorinated paraffines helps you to fulfil aspects of legislative requirements and waste treatment requirements that specify that this chemical is excluded
- Low odor, light color and low mist qualities can lead to high operator acceptability

Typical Characteristics

Properties	Standard	Unit	Data
Appearance	Visual		Amber/Yellow
Viscosity @ 40°C	DIN 51562 ASTM D 445	mm ² /s	14
Density @ 15°C	DIN 51757 ASTM D 1298	kg/l	851
Flashpoint COC	DIN EN ISO 2592 ASTM D 92	°C	196°C
Copper corrosion 3 hr at 100 °C 3 hr at 50° C 3 hr at RT	DIN EN ISO 2160 ASTM D 130		4a 1b 1b

Subject to usual manufacturing tolerances.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

Variocut C 814 HC
12 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>